

Open Gear

5100-5182 PYROSHIELD® Lubricant technology from LE provides one lubricant for the mining and mineral processing industry, open gears and other similar applications. An extremely high load-carrying, lead-free lubricant developed to operate in severe (heavy) service.

- Extreme pressure, lead-free lubricant with superb load carrying capacity
- Operates in both mobile and stationary equipment inside and outside
- Formulated with high viscosity, 100% synthetic base oil, non-melting thickening system and heat stable additives for high temperature applications
- Excellent in low temperature applications
- Convenient aerosol can contains no ozone depleting chemicals
- Outstanding wear reduction
- Resists shock loading
- Bentone thickener
- Water, heat and load resistant
- Excellent choice for open gears, chains, cables, fifth wheels and pinions, and various sliding mechanisms
- Excellent adhesive properties

Technical Information

Product Information 9102 SYNTEMP® Synthetic Lubricant Unique, heavy-duty, spray lubricant designed for open gears, chains, cables, sealed bearings and slides. Withstands high temperatures, won't sling off. In a convenient aerosol can.

- Heavy duty aerosol synthetic for use on high temperature chains, sprockets, slides and other applications
- Clean and easy to apply
- Very tacky, won't run or melt
- Superior lubricating qualities reduce wear, friction and heat far more effectively than other synthetic and petroleum grease
- Water resistant
- Rust and oxidation resistant, mechanically stable
- Extreme Pressure and exclusive wear-reducing additives
- High load carrying ability
- Wide temperature range
- Contains no ozone depleting chemicals

Technical Information

Product Information 9901 ALMASOL® SYNTEMP LUBRICANT Heavy-duty synthetic lubricant specifically designed for high temperature applications. Specially formulated to provide exceptional protection at temperatures at which petroleum oils would completely oxidize (or carbonize).

- High temperature lubricant made from a very heavy synthetic fluid and non-melting base
- Formulated to provide exceptional protection at temperatures at which petroleum oils would completely oxidize
- Excellent for use on large open gears exposed to very high temperatures
- Recommended for use on kiln girth gears, large industrial gearing, oven chains, sliding surfaces, large slow moving bearings and similar applications
- Bentone thickener
- Contains ALMASOL®, LE's exclusive wear-reducing additive

Technical Information

Product Information