

General Purpose

1232 ALMATEK® General Purpose Lubricant A technologically advanced lubricant designed to withstand water washout, shock loading and pounding out in bearings, chassis points and other grease lubricated applications.

- Highly versatile general-purpose lubricant for friction and anti-friction bearings, chassis points, and other grease lubricated applications
- Semi-tacky
- Resists wash out, shock loading and pound out
- Ball, roller and plain bearings operate cooler
- Very good pumpability at lower temperatures
- High dropping point
- Lowers operating temperatures in severe service
- Lithium 12-hydroxy thickener
- Contains ALMASOL®, LE's exclusive wear-reducing additive

Technical Information

Product Information 1274-1275 ALMAPLEX® Industrial Lubricant The truly versatile bearing lubricant for all industries. An excellent general purpose extreme pressure (EP) lubricant for industrial or fleet use. Very effective in severe operations caused by moisture or high temperatures.

- Excellent general purpose EP lubricant for industrial or fleet use
- Seals out dirt and water
- Prevents corrosive wear
- Timken OK load of 45 lbs
- Excellent for electric motors, machine tools, presses, forging equipment, metal fabrication, and wood working
- Can be used in central lubrication systems
- Excellent reversibility
- Bearings operate cooler
- Very high dropping point
- Excellent oxidation resistance and rust protection
- Retains soft body and plasticity much longer than ordinary greases
- Good low temperature pumpability
- Aluminum complex thickener
- Contains ALMASOL®, LE's exclusive wear-reducing additive

Technical Information

Product Information 3750-3752 ALMAGARD® Vari-Purpose Lubricant An extreme pressure (EP) lubricant, for extended service, that won't wash off, pound out, or melt and run, even with extended service in severe conditions.

- Multi-functional, EP lubricant for extended service under extreme conditions
- Use in all types of vehicles, on and off road, as well as in-plant applications
- Very tacky
- Excellent water resistance
- Will not pound out
- Rust and corrosion inhibited
- Extremely versatile
- Great oxidation stability and longer life, does not "work down" in service
- High dropping point
- Good heat reversion
- Does not harden on aging, easily pushed out by fresh grease
- Timken OK load of 70 lbs
- Bearing life may be extended up to three times with cooler operation
- Reduces downtime and maintenance labor because of smooth, cool performance
- Lithium complex thickener
- Contains ALMASOL®, LE's exclusive wear-reducing additive

Technical Information

Product Information 4622 MONOLEC® Multiplex Lubricant High quality, lithium complex grease that meets the requirements of the NLGI GC-LB specification. Excellent low temperature pumpability for cold weather applications.

- Works well in plain and anti-friction bearings
- Perfect for use in industrial, fleet and automotive applications calling for an EP grease
- Good mechanical stability and a high dropping point
- Pumps easily at low temperatures
- Contains both extreme pressure and antiwear additives

- Protects bearings from rust and corrosion
- Contains MONOLEC®, LE's exclusive wear-reducing additive

Technical Information

Product Information 4700-4702 MONOLEC® Industrial Lubricant Designed especially for centralized lubrication systems. Waterproof and will not form permanent emulsions where moisture is present.

- Industrial lubricant specialized products for centralized lubrication systems and where a medium EP grease is used
- Water resistance
- High heat resistance
- Low separation or "bleed"
- Excellent mechanical stability
- Easily pumpable
- Long life in centralized lube systems
- 450°F (230°F) dropping point
- Does not harden on aging, easily pushed out by fresh grease
- Timken OK load of 45 lbs
- Reduces downtime and labor because of smooth, cool performance
- Aluminum complex thickener
- Contains MONOLEC®, LE's exclusive wear-reducing additive

Technical Information

Product Information